



POWERED BY



TECHNOLOGY

HP FRAC VALVE GREASE SEALANT

HP FRAC VALVE GREASE SEALANT

POWERED BY



TECHNOLOGY

Permian Production Lubricants' PXP HP 3.5 is a high performance frac valve grease delivering extreme adhesion and resistance to washout, frac chemicals, corrosion, friction reducers, and brines. PXP HP 3.5 Valve Grease / Sealant is a proprietary blend of PXP Extreme Pressure additive, moly complex, graphite, and corrosion inhibitors.

Current customers report a dramatic improvement in valve wear, performance, maintenance, and consumption rates along with enhanced value at its aggressive price point.



**#MOLY COMPLEX W/
PXP & GRAPHITE FOR
MAXIMUM ADHESION**

Extremely tacky thick grease with Permian Extreme Pressure (PXP) additive for increased metal surface protection from scoring, wear, and corrosion.



**HIGHLY RESISTANT TO
HVFR & WELL FLUIDS**

Formulated with the toughest proprietary additive packs to provide additional resistance to High Viscosity Friction Reducers, Sour Gas, Acids, Frac Fluids, CO₂, Biocides, H₂S, and salt water



**WITHSTANDS
OVER 18,000 PSI
HYDROSTATIC PRESSURE**

With water washout at under 2% PXP HP displays tremendous resistance against erosion by fresh and brine water to prevent leaks and reduced consumption.

FEATURES & BENEFITS

- Extremely Tacky, highly adhesive
- Prevents Leaks
- Reduces Consumption
- Reduces Valve Wear & Maintenance
- Excellent Sealing Capability
- Ease of Pumpability
- Organic and Inorganic Fluids Resistance

CHARACTERISITICS

TEST METHOD	PPL FRAC VALVE GREASE & SEALANT
Appearance	Semi Plastic
NLGI Grade	3.5
Color	Black
Thickener Type	Organic Moly Complex
Additives	PXP, graphite, other corrosion and chemical inhibitors
Temp Range	+15F to +400F
Density	950/kg
Cone Penetration: ASTM D-217	280-320

4,500 LB. CAPACITY DUAL PUMP GREASE DISPENSER

ACCEPTS ULTRA HIGH PRESSURE AND STANDARD TRANSFER PUMPS



Our dispensing system is a major improvement to the greasing efficiency at the wellhead, while holding an average of 1,500 lbs. more grease than round poly totes. The Hot Box is a multi function, valve greasing system with both 3" standard transfer pump, and 3" UHP pump ports for direct greasing, which eliminates waste, mess, and trash. The internal heaters, keep warm grease pumping in colder weather, and the sealed dispensing system eliminates contaminants and airlock issues.

- Pump direct and bypass intermediate transfer containers
- Sealed and secure dispenser eliminates air lock, and air gaps
- Reduce pump failures by reducing contaminants from sand and air
- Diamond shaped bottom keeps grease weight at the pump
- Ultra High Pressure Pump compatible to pump at 99% of grease
- Holds 36% more grease than poly cylinder totes
- Eliminate contaminants common in floating lid totes
- Reduces oil field, trash, drums, and totes
- Dramatic reduction in grease waste disposal costs
- Your customers appreciate the cleaner appearance on the pad.

ASK ABOUT OUR DISPENSER EXCHANGE PROGRAM

ABOUT US

Permian Production Lubricants is a West Texas based lubricant company, utilizing its proprietary, Permian Extreme Pressure (PXP) cationic EP additive to differentiate the performance of its products. The result is improve performance, and efficiency, while reducing consumption, where, and failure rates. The company is extremely focused on movement and application specific solutions for completions equipment.



(432) 223-0200



www.permianlubes.com